

Printer Data Sheet

Name		Thermal Printer PES-236L-C
Photo		  White color Black color
Production		Suzhou /China
Print	Printing Method	Direct Thermal Printing
	Printing Speed	Max. 80mm/s
	Resolution	203dpi
	Effective Printing Width	48mm
Character	Character Set	GB2312, 16x16dots, or 24x24dots
	Character	8x16dots, or 12x24dots , 9x17dots
	Character per Line	32
Paper Spec	Paper Type	Thermal paper
	Paper Width	57.5± 0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Paper Thickness	0.06 to 0.1mm
	Paper out detection	Support
Paper Supply Method		Drop-in Paper Load

Thermal Print header		CKANPLUS
Cutter		Manual
Printer Head Life		50km Printing length
Bar code type		125, UPC-A, UPC-E, EAN-8, EAN-13, Codebar, Code39, Code93, Code128, Code11, MSI
Emulation		ESC/POS
Driver		WIN2003/WINXP/WIN7/WIN8/WIN10
Drawer Port		1 Port
Interface		USB;RS232
Input Power		12-24V,1A
Working Temperature		-10 ~ 50 °C
Working Humidity		RH 20 ~ 90%
Storage Temperature:		-20 ~ 70°C
Storage Humidity		RH 5 ~ 95%
Physical	Gross Weight	0.3kg
	Printer Dimension	115(L)×86.2(W)×132mm(H)