

Printer Data Sheet

Name		Thermal Printer PDS-335H-C
Photo		 White color  Black color
Production		Suzhou /China
Print	Printing Method	Direct Thermal Printing
	Printing Speed	Max. 250mm/s
	Resolution	203dpi
	Effective Printing Width	72mm
Character	Character Set	GB2312, 16x16dots, or 24x24dots
	Character	8x16dots, or 12x24dots , 9x17dots
	Character per Line	32
Paper Spec	Paper Type	Thermal paper
	Paper Width	79.5± 0.5mm
	Paper Roll Diameter	Max: 80.0mm
	Paper Thickness	0.06 to 0.12mm
	Paper out detection	Support
Paper Supply Method		Drop-in Paper Load
Thermal Print header		CKANPLUS

Cutter		Auto cutter : 1.5 million cuts (Full cutter/Half cutter as options)
Printer Head Life		150km Printing length
Bar code type		125, UPC-A, UPC-E, EAN-8, EAN-13, Codebar, Code39, Code93, Code128, Code11, MSI
Emulation		ESC/POS
Driver		WIN2003/WINXP/WIN7/WIN8/WIN10
Drawer Port		1 Port
Interface		USB;
Input Power		24V,2A
Working Temperature		-10 ~ 50 °C
Working Humidity		RH 20 ~ 90%
Storage Temperature:		-20 ~ 70°C
Storage Humidity		RH 5 ~ 95%
Wall Mount Function		Support
Physical	Gross Weight	1.05kg
	Printer Dimension	132.6(L)×135(W)×133mm(H)