

## **CKANPLUS SBE-5325-U**

The Ckanplus' Big eye series point-of-sale hands free/presentation scanner is the perfect blend of affordability, performance and style. scale commercial deployment.




SBE-5325 with the Ckanplus leading scanning technology, it can easily handle damaged and blurred barcodes. The wide-angle camera enables normal reading even when the barcode is close.

Equipped with a 1-megapixel image sensor and high-speed processor, it features fast reading speed and can adapt to higher motion tolerance, there by reducing repeated scanning and maintaining work efficiency.

### **Make scanning faster and easier!**

#### **Product Features:**



Equipped with a 1-megapixel image sensor and high-speed processor, to support outstanding motion tolerance, Broader Field of view-



With Ckanplus' intelligent software tools, the configuration and installation process can be simplified.



Easy to be compatible with various POS machines and devices, making it convenient to use.

### **Physical Characteristics:**

Dimensions: 186mm x 152mm x 87mm

Voltage: 5V

Weight: 437g

### **Performance:**

<b>Starting Current:</b>	500mA
<b>Stand-by Current</b>	500mA
<b>Operating current</b>	380mA
<b>Image (Pixels)</b>	1280*1024
<b>Exposure mode</b>	Global shutter
<b>Light Source</b>	(Illumination) Warm Red color LED
<b>Field of View</b>	39°(Horizontal), 28°(Vertical)
<b>Print Contrast</b>	20% minimum
<b>Motion Tolerances</b>	4.0m/s
<b>Minimum Resolution</b>	≥4mil
<b>DOF (depth of field)</b>	<b>Code39(5mil)</b> 0mm-70mm
	<b>Code39(13mil)</b> 0mm-170mm
	<b>PDF417: 6.7mil</b> 0mm-80mm
	<b>QR code(20mil)</b> 0mm-140mm
	<b>UPC-A(13mil)</b> 0mm-160mm
<b>Designed to withstand drops</b>	0.7m
<b>Operating Temperature</b>	Range: -20°C to 60°C
<b>Interface</b>	USB
<b>IP</b>	IP42

### **Decode Capability:**

1D: Codabar、Code 39、Code 32 Pharmaceutical (PARAF)、Interleaved 2 of 5、NEC 2 of 5、Code 93、Straight 2 of 5 Industrial、Straight 2 of 5 IATA、Matrix 2 of 5、Code 11、Code 128、GS1-128、UPC-E、EAN/JAN-8、EAN/JAN-13、MSI、GS1 DataBar Omnidirectional、GS1 DataBar Limited、GS1 DataBar Expanded、China Post(Hong Kong 2 of 5)、Korea Post.

2D: Codeblock A、Codeblock F、PDF417、Micro PDF417、GS1 Composite Codes、QR Code、Data Matrix、MaxiCode、Aztec、HANXIN

### **User Environment:**

Operating Temperature : -20°C to 60°C

Storage Temperature : -30°C to 70°C

Humidity : 5% to 95% relative humidity,non-condensing

Shock Specifications : Designed to withstand 0.7m(5' ) drops

Ambient Light Immunity :0-100,000 Lux.

**Dimension (unit:mm)**

