

Printer Data Sheet

Name		Thermal Printer PAT-230H-C
Photo		
Production		Suzhou /China
Print	Printing Method	Direct Thermal Printing
	Printing Speed	Max. 200mm/s
	Resolution	203dpi
	Effective Printing Width	54mm
Character	Character Set	GB2312, 16x16dots, or 24x24dots
	Character	8x16dots, or 12x24dots , 9x17dots
	Character per Line	32
Paper Spec	Paper Type	Thermal paper
	Paper Width	59.5± 0.5mm
	Paper Roll Diameter	Max: 120.0mm
	Paper Thickness	0.1mm
	Paper out detection	Support
Paper Supply Method		Drop-in Paper Load

Thermal Print header		CKANPLUS
Cutter		Auto cutter : 1.0 million cuts (Full cutter/Half cutter as options)
Printer Head Life		200km Printing length
Paper feeding method		Automatic paper suction (horizontal 180°)
Baud rate		9600、19200、38400、115200
Switch lock key		Support
Bar code type		125, UPC-A, UPC-E, EAN-8, EAN-13, Codebar, Code39, Code93, Code128, Code11, MSI
Emulation		ESC/POS
Driver		WIN2003/WINXP/WIN7/WIN8/WIN10
Interface		USB;RS232
Input Power		24V,2A
Working Temperature		-10 ~ 50 °C
Working Humidity		RH 20 ~ 90%
Storage Temperature:		-20 ~ 70°C
Storage Humidity		RH 5 ~ 95%
Physical	Gross Weight	1.8kg
	Printer Dimension	110(L)×200.8(W)×135.2mm(H)