

CKANPLUS Product Catalog

Model name: *CAF-300R-PoE*



Key Specifications:

Category	Item	Specification
System	System Processor	Embedded Linux architecture, A7 1GHz processor
	Image Sensor	1/2.9" Low illuminance CMOS sensor
Image	Streams	Dual stream
	Main Stream Frame Rate & Resolution	20fps: 2304×1296 (default), 2304×1296, 1920×1080
	Sub Stream Frame Rate & Resolution	20fps: 720×576, 720×480, 704×576 (default), 640×360, 640×480, 512×288, 352×288
	Effective Pixels	3 Megapixels
	Video Compression Standard	H.265 (default) / H.264
	Bitrate	Main Stream: 256~8192Kbps (default 3072Kbps) Sub Stream: 68~1024Kbps (default 682Kbps)
	Wide Dynamic Range	Digital WDR
	Signal-to-Noise Ratio	49dB
	Minimum Illumination	0 Lux (with supplementary light ON)
Supplementary Light	Light Adjustment	Adaptive brightness adjustment
	Light Modes	IR light, warm light, smart dual light (default), light off
Image	Image Style	Supports standard, soft, clear

Processing	Day/Night Mode Switching	Auto, Scheduled, Day Mode, Night Mode
	Image Adjustment	Supports contrast, brightness, saturation, sharpness
	Exposure Settings	Auto
	Image Enhancement	Digital 3D noise reduction, dehazing
Audio	Audio Stream	Enabled by default; can be disabled
	Encoding Format	G711A (default) / G711U
Network	Concurrent Streams	Up to 16 client streams
	Browser Support	IE8+, Chrome18+, Firefox5.0+, Safari5.02+; supports Chinese & English
	API Protocols	Standard ONVIF
	Network Protocols	Standard HTTP, TCP/IP, ICMP, RTSP, RTP, UDP, RTCP, SMTP, DHCP, DNS
	Connection Method	Wired
Interfaces	Audio	1 built-in MIC, 1 built-in speaker
	Network	1 RJ45 10M/100M adaptive Ethernet port
General	User Management	Up to 12 users, 3-level permissions: Admin, User, Visitor
	General Functions	Time settings, OSD settings, privacy masking, log management, tampering alarm, defocus detection
	Factory Reset	Via browser or mobile app
	Operating Temperature/Humidity	-20°C ~ +60°C; 10% ~ 90% RH
	Power Supply	PoE or DC 12V

Pin Definition:

Label	Silkscreen No.	Pin No.	Pin Definition	Function
Power & Network	J3	1	78	Network 7 & 8 (PoE Spare Pair)
		2	45	Network 4 & 5 (PoE Spare Pair)
		3	TNTX+	Network 1 (Transmit +)
		4	TNTX-	Network 2 (Transmit -)
		5	TNRX-	Network 3 (Receive -)

		6	TNRX+	Network 6 (Receive +)
		7	GND	Ground
		8	12V	12V Power Input
LED Board	J9	1	LED_IR	IR LED Control
		2	LED_W	White Light Control
		3	GND	Ground
		4	12V	12V Power Supply
		5	3V3	3.3V Power Supply
		6	LED_RED	Status Indicator LED
Audio I/O	J24	1	AC_OUT	Audio Output
		2	GND	Ground
		3	AC_IN	Audio Input
		4	GND	Ground
Microphone	J4	1	GND	Ground
		2	MIC+	Microphone Positive
Speaker	J8	1	SPK-	Speaker Negative
		2	SPK+	Speaker Positive
Net LED & Reset	J25	1	RECOVERY	Reset / Factory Restore
		2	LINK	Network Link Indicator
IR-CUT	J5	1	BOUT	IR-CUT Drive B
		2	AOUT	IR-CUT Drive A
Photosensitive	J23	1	GND	Ground
		2	CDS+	Photosensitive Sensor
Expansion Slot	J22	1	12V	12V Power
		2	12V	12V Power
		3	GND	Ground
		4	3V3	3.3V Power
		5	ALARM_IN	Alarm Input
		6	ALARM_OUT	Alarm Output
		7	GND	Ground
		8	USB_DP	USB Data Plus
		9	USB_DM	USB Data Minus
		10	GND	Ground
		11	WIFI_EN	4G or Wi-Fi Enable
		12	SDIO0_CDATA2	SD Data 2
		13	SDIO0_CDATA3	SD Data 3
		14	SDIO0_CCMD	SD Command (CMD)

		15	GND	Ground
		16	SDIO0_CCLK_OUT	SD Clock
		17	SDIO0_CDATA0	SD Data 0
		18	SDIO0_CDATA1	SD Data 1
		19	SDIO0_CARD_DETECT	SD Card Detection
		20	SDIO0_CARD_POWER_EN	SD Power Enable
		21	UART2_RXD	RS485 Receive
		22	UART2_TXD	RS485 Transmit
		23	UART2_RTSN	RS485 Control (Direction)
		24	RECOVERY	Reset / Factory Restore

Mechanical Dimension:

