


## Printer Data Sheet

<b>Name</b>		<b>Thermal Printer PAT-330H-C3</b>
<b>Photo</b>		
<b>Production</b>		Suzhou /China
<b>Print</b>	Printing Method	Direct Thermal Printing
	Printing Speed	Max. 250mm/s
	Resolution	203dpi
	Effective Printing Width	80mm
<b>Character</b>	Character Set	GB2312, 16x16dots, or 24x24dots
	Character	8x16dots, or 12x24dots , 9x17dots
	Character per Line	32
<b>Paper Spec</b>	Paper Type	Thermal paper
	Paper Width	82mm
	Paper Roll Diameter	Max: 150mm
	Paper Thickness	0.06 to 0.2mm
	Paper out detection	Support
<b>Paper Supply Method</b>		Drop-in Paper Load
<b>Thermal Print header</b>		CKANPLUS
<b>Cutter</b>		Auto cutter : 1.0 million cuts

<b>Printer Head Life</b>	100km Printing length	
<b>Bar code type</b>	UPC-A; UPC-E; EAN-8; EAN13; CODE39; ITF; CODEBAR; CODE128; CODE93; QR CODE; PDF417	
<b>Emulation</b>	ESC/POS	
<b>Driver</b>	WIN2003/WINXP/WIN7/WIN8/WIN10	
<b>Drawer Port</b>	1 Port	
<b>Interface</b>	USB;RS232	
<b>Input Power</b>	24V,2A	
<b>Working Temperature</b>	-10 ~ 50 °C	
<b>Working Humidity</b>	RH 20 ~ 90%	
<b>Storage Temperature:</b>	-20 ~ 70°C	
<b>Storage Humidity</b>	RH 5 ~ 95%	
<b>Wall Mount Function</b>	No	
<b>Physical</b>	Gross Weight	1.45kg
	Printer Dimension	112(L)×190(W)×84mm(H)

**Pin definition:**

<b>USB/SERIAL 引脚定义 (RJ11)</b>	
<b>Pin number</b>	<b>Signal name</b>
1	VUSB
2	D-
3	D+
4	GND
5	TXD
6	RXD

<b>直流电源插座 (5557-2PIN)</b>	
<b>Pin number</b>	<b>Signal name</b>
1	VH(DC24V 2A)
2	GND

Dimension:

