

## Printer Data Sheet

<b>Name</b>		<b>Thermal Printer PAT-330H-C</b>
<b>Photo</b>		
<b>Production</b>		Suzhou /China
<b>Print</b>	Printing Method	Direct Thermal Printing
	Printing Speed	Max. 250mm/s
	Resolution	203dpi
	Effective Printing Width	80mm
<b>Character</b>	Character Set	GB2312, 16x16dots, or 24x24dots
	Character	8x16dots, or 12x24dots , 9x17dots
	Character per Line	32
<b>Paper Spec</b>	Paper Type	Thermal paper
	Paper Width	80± 2mm
	Paper Roll Diameter	Max: 120.0mm
	Paper Thickness	60-150um
	Paper out detection	Support
<b>Paper Supply Method</b>		Drop-in Paper Load
<b>Thermal Print header</b>		CKANPLUS
<b>Cutter</b>		Auto cutter : 1.0 million cuts

		(Full cutter/Half cutter as options)
<b>Printer Head Life</b>		200km Printing length
<b>Paper feeding method</b>		Automatic paper suction (horizontal 180°)
<b>Baud rate</b>		9600、19200、38400、115200
<b>Switch lock key</b>		Support
<b>Bar code type</b>		125, UPC-A, UPC-E, EAN-8, EAN-13, Codebar, Code39, Code93, Code128, Code11, MSI
<b>Emulation</b>		ESC/POS
<b>Driver</b>		WIN2003/WINXP/WIN7/WIN8/WIN10
<b>Interface</b>		USB;RS232
<b>Input Power</b>		24V,2A
<b>Working Temperature</b>		-10 ~ 50 °C
<b>Working Humidity</b>		RH 20 ~ 90%
<b>Storage Temperature:</b>		-20 ~ 70°C
<b>Storage Humidity</b>		RH 5 ~ 95%
<b>Physical</b>	Gross Weight	2.5kg
	Package Dimension	40(L)×30(W)×40cm(H)